

WithSecure Cloud Protection for Salesforce Administrator's Guide

Contents

Chapter 1: Solution overview.....	4
1.1 Features.....	5
Chapter 2: Deployment.....	6
2.1 Supported Salesforce editions.....	7
2.2 Prerequisites.....	7
2.2.1 Turn the Chatter feature on.....	7
2.2.2 Allow editing of posts and comments in Chatter settings.....	7
2.2.3 Allow uploading of attachments as Salesforce files.....	7
2.2.4 Activating other languages.....	8
2.3 Installing the application.....	8
2.4 Assigning permission sets and licenses.....	9
2.4.1 Assign WithSecure Cloud Protection User permission set.....	9
2.4.2 Assign WithSecure Cloud Protection Admin permission set.....	9
2.4.3 Assign WithSecure Cloud Protection licenses.....	9
2.5 Upgrading the application.....	10
Chapter 3: Configuring the application settings.....	12
3.1 Configuring recipients for alerts and notifications.....	13
3.2 Configuring security alerts and warning messages.....	13
3.3 Setting up file protection.....	14
3.4 Setting up URL protection.....	15
3.5 Changing the settings for manual and scheduled scanning.....	15
3.6 Creating a permission set for manual scanning.....	16
3.7 Setting up automatic product updates.....	17
3.8 Changing the privacy settings.....	17
Chapter 4: Using the application.....	18
4.1 Excluding files from the scan.....	19
4.2 Scanning for harmful content in your Salesforce organization manually.....	19
4.3 Scanning for harmful content at set times.....	19
4.4 Using the quarantine.....	20
4.5 Viewing alerts and using the search.....	20
4.6 Viewing and editing reports.....	21
4.7 Clearing the scan result cache.....	23
4.8 Viewing license information for the product.....	23
Chapter 5: Testing the application.....	24
5.1 Testing the file protection.....	25

5.2 Testing the URL protection.....25

Chapter 6: Uninstallation.....26

6.1 Removing permission set assignments.....27

6.2 Uninstalling the application.....27

Chapter 1

Solution overview

Topics:

- [Features](#)

WithSecure Cloud Protection for Salesforce is a cloud-based security solution that is designed to improve and extend the native security capabilities of the Salesforce platforms.

WithSecure Cloud Protection for Salesforce analyzes the content that enters or leaves the Salesforce cloud, so that files and URLs that are uploaded or downloaded from a Salesforce organization cannot be used in cyber attacks against your company, partners, or customers.

The solution comprises a native Salesforce application and WithSecure Security Cloud that provides file and website reputation and security services. The WithSecure Cloud Protection application is installed on Salesforce Sales, Service, or Experience Cloud (previously known as Community Cloud) that your company uses. You do not need to install any other software or make any changes to your network configuration.

WithSecure Security Cloud is a cloud-based threat analysis and response system. It analyzes the threat intelligence that is gathered by our millions of sensor nodes, creating a vast database of digital threats that builds a real-time picture of the global threat situation.

WithSecure Cloud Protection for Salesforce leverages this data to respond to changes in the global or local threat landscape within minutes. For example, when our heuristic and behavior analysis identifies a new zero-day attack, the information is shared with all our customers - rendering the advanced attack harmless very soon after the initial detection.

The solution is designed to reduce delays and it does not hinder the use of Salesforce. When analyzing files or content, the solution uses a multi-stage process that leverages WithSecure Security Cloud. The steps within this process are triggered based on the risk profile of the content. For example, only high-risk files go through a deeper analysis with our Smart Cloud Sandboxing technology, which is designed to prevent attacks using zero-day malware and other advanced threats.

1.1 Features

WithSecure Cloud Protection for Salesforce is the ideal solution to handle your part of security under the Shared Responsibility model. It provides more than a simple antivirus software ever will. The solution integrates seamlessly with Salesforce and requires no middleware.

File protection	The solution provides advanced protection for files inside Salesforce. It protects them against malware, ransomware, exploits, and other advanced threats. It automatically scans uploaded and downloaded files with minimal impact on performance and user experience.
URL protection	The solution analyzes and blocks access to malicious URLs before they can compromise your network. The analysis is done with zero latency and requires very few resources.
Threat intelligence check	By leveraging real-time threat intelligence that is gathered from tens of millions of sensors, we can identify emerging and new threats within minutes of their inception, ensuring exceptional security against constantly evolving threats.
Multi-engine advanced antivirus	WithSecure technologies use behavioral analysis and multiple security layers to detect exploits and unknown malware that are used in targeted attacks.
Smart cloud sandboxing	When a high-risk file is found, it is subjected to deeper analysis with WithSecure Smart Cloud Sandboxing technology, blocking zero-day malware and advanced threats without any unnecessary delays.
Content filtering	The solution allows the detection and blocking of dangerous and inappropriate content that is not allowed according to security or compliance policies. Disallowed files can be filtered out based on the file type or file extension.
On-demand and scheduled scanning	Salesforce files and attachments can be scanned for harmful and disallowed content at any time or at predefined intervals. You can choose which files are scanned based on the creation or modification time, file type, or location.
Quarantine management	Harmful or disallowed content removed by File Protection can be viewed and restored with the quarantine management tool.
File replacement in alert details	When harmful content is removed and replaced by a text file, the object ID of the replacement file is reported in the alerts details.
Dynamic analytics and reporting	Dynamic analytics and reporting gives a holistic security overview of Salesforce content and an opportunity to follow your security strategy in action. Rich reporting, advanced security analytics, and full audit trails help system administrators to respond to threats in Salesforce and to investigate attacks coming from unknown sources.
Alerting	You can automate reports of security incidents with email alerts that are sent to administrators and your security department.
Automatic updates	You can receive the new version of the app to your sandbox and production organizations automatically based on your preferences.
Scan page customization	The product banner shown on the scan pages can be customized. The organization can also change messages shown to the end users when harmful or disallowed content is blocked.
Scalable licensing	WithSecure offers a predictable licensing model based on your actual network traffic.
Automatic license assignment	Application licenses can be automatically assigned as standard user, community user, and community login user licenses to Salesforce users based on user profiles or other criteria.
Quick and easy installation	The installation takes only a few minutes from Salesforce AppExchange. You do not need to install any software on end-user devices, deploy any proxies, or make any MX changes.
Lightning ready	The application supports both Salesforce Classical and Lightning Experience User Interface.

Chapter 2

Deployment

Topics:

- [Supported Salesforce editions](#)
- [Prerequisites](#)
- [Installing the application](#)
- [Assigning permission sets and licenses](#)
- [Upgrading the application](#)

This section provides instructions for deploying WithSecure Cloud Protection in your Salesforce organization.

Deploying the application involves the following steps:

- Installing the application
- Assigning permission sets and licenses
- Configuring the application settings

If you are upgrading from the previous version, see [Upgrading the application](#) on page 10.

2.1 Supported Salesforce editions

The WithSecure Cloud Protection application supports Salesforce Classic and Lightning Experience user interfaces, and can be installed to the Salesforce Editions listed here.

- Enterprise
- Performance
- Unlimited
- Developer Edition

Note: We highly recommend that you verify the application in a sandbox before you deploy it to your production environment.

2.2 Prerequisites

Check the Salesforce settings here before you start to install WithSecure Cloud Protection for Salesforce.

2.2.1 Turn the Chatter feature on

To install and use WithSecure Cloud Protection, the Chatter feature must be on in your Salesforce organization.

To turn on the Chatter feature:

1. Log in to Salesforce with your System Administrator account.
2. Go to your organization settings and select **Setup**.
3. Navigate to **Feature Settings > Chatter > Chatter Settings**.
4. Select **Edit** to change the settings.
5. Select **Enable** under **Chatter Settings** and then select **Save**.

2.2.2 Allow editing of posts and comments in Chatter settings

To prevent broken user mentions in the Chatter posts and comments, we highly recommend that you turn on the **Allow users to edit posts and comments** setting in the Chatter settings.

To turn this setting on in your Salesforce organization:

1. Log in to Salesforce with your System Administrator account.
2. Go to your organization settings and select **Setup**.
3. Navigate to **Feature Settings > Chatter > Chatter Settings**.
4. Select **Edit** to change the settings.
5. Under **Post and Comment Modification**, select **Allow users to edit posts and comments** and then select **Save**.

2.2.3 Allow uploading of attachments as Salesforce files

If you are storing files as attachments and use Salesforce Classic user interface, we recommend that you turn on the **Files uploaded to the Attachments related list on records are uploaded as Salesforce Files, not as attachments** setting.

By turning on this setting, files that are uploaded as attachments are converted to Salesforce files and scanned by WithSecure Cloud Protection when uploaded or downloaded.

To turn this setting on in your Salesforce organization:

1. Log in to Salesforce with your System Administrator account.
2. Go to your organization settings and select **Setup**.
3. Navigate to **Feature Settings > Salesforce Files > General Settings**.
4. Select **Edit** to change the settings.
5. Select **Files uploaded to the Attachments related list on records are uploaded as Salesforce Files, not as attachments** and then select **Save**.

2.2.4 Activating other languages

The default language for WithSecure Cloud Protection is English, but you can also activate other supported languages.

WithSecure Cloud Protection currently supports the following languages:

- Chinese (Simplified)
- Chinese (Traditional)
- Czech
- English
- French
- German
- Hungarian
- Italian
- Japanese
- Korean
- Polish
- Portuguese
- Russian
- Slovak
- Spanish
- Thai
- Turkish

Note: The administrator's selected language during installation is used as the default language for alerts.

To activate other languages:

1. Log in to Salesforce with your System Administrator account.
2. Go to your organization settings and select **Setup**.
3. Select **User Interface > Translation Workbench > Translation Settings** from the menu.
4. Select the **Active** checkbox for the language that you want.

Users within your organization can now use WithSecure Cloud Protection in the activated language if they have selected that language in their account settings, under **Settings > My Personal Information > Language & Time Zone**.

2.3 Installing the application

Follow these instructions to install the application to your Salesforce organization.

1. Log in to Salesforce with your System Administrator account.
2. Go to the Salesforce AppExchange marketplace, find the WithSecure Cloud Protection application, and select **Get It Now** to start the installation.

WithSecure Cloud Protection is listed on Salesforce AppExchange here:

<https://appexchange.salesforce.com/listingDetail?listingId=a0N3A00000EFntJUAT>.

Note: If you are installing a release preview or beta version of the WithSecure Cloud Protection application, you will receive a direct link to the managed installation package. To start the installation, open the link in your web browser.

Note: If you already have a release preview or beta version of the application installed, uninstall it before you install the new version of the application.

3. Depending on whether you are installing the application to your production Salesforce org or Sandbox, choose **Install in production** or **Install in Sandbox**.
4. Check the installation details.
5. Select **I have read and agree to the terms and conditions** and then select **Confirm and Install**.
6. Select **Install for Admins Only** and then select **Install**.
7. Select **Yes, grant access to these third-party web sites** to allow the application to connect to the WithSecure Security Cloud services. Then, select **Continue**.
8. Wait until the installation is complete.

Important: If you receive a message that the app is taking too long to install, wait for a confirmation email from Salesforce that the app has been installed.

9. Select **Done** when the installation is complete.

WithSecure Cloud Protection has been installed successfully.

2.4 Assigning permission sets and licenses

After you have installed the application, you need to assign WithSecure Cloud Protection permission sets and licenses.

2.4.1 Assign WithSecure Cloud Protection User permission set

You need to assign the WithSecure Cloud Protection User permission set to all active users within your organization even if you do not have WithSecure software license purchased for some of them.

Follow these instructions to assign the WithSecure Cloud Protection User permission set.

1. Log into Salesforce with your System Administrator account.
2. Go to **App Launcher** and open **Cloud Protection**.
3. Go to **Administration > Tools** and select **Assign** under **Manage user permission set**.

All active users within your Salesforce organization get the WithSecure Cloud Protection User permission set assigned.

Note: The permission set is assigned to active users in the background.

4. Under **Administration > Tools**, select **Enable** to turn on the automatic assignment of the WithSecure Cloud Protection User permission set to new users who are added to your Salesforce organization after the WithSecure application has been installed.

Tip: We recommend that you keep this option turned on.

The app creates informational alerts when the tasks are activated and complete.

If the assignment of the WithSecure permission set fails, the app generates an error alert with a list of user IDs that did not receive the permission set.

2.4.2 Assign WithSecure Cloud Protection Admin permission set

You need to assign WithSecure Cloud Protection Admin permission set to users who are allowed to access the application settings, analytics, and reports.

Follow these steps to assign the WithSecure Cloud Protection Admin permission set:

1. Log into Salesforce with your System Administrator account.
2. Go to your organization settings and select **Setup**.
3. Select **Users > Permission Sets > WithSecure Cloud Protection Admin**.
4. Select **Manage Assignments**.
5. Select **Add Assignments**.
6. Select all the users who need to access the WithSecure Cloud Protection application, analytics, and reports, and then select **Add Assignments**.

2.4.3 Assign WithSecure Cloud Protection licenses

WithSecure Cloud Protection licenses must be assigned to all users who administer the application or who are protected against security threats associated with harmful and disallowed content.

Note: Users without assigned WithSecure licenses are not protected by WithSecure Cloud Protection. They are at risk of accessing harmful or disallowed content that may get into your Salesforce organization

Follow the steps below to assign WithSecure Cloud Protection licenses to your users:

1. Log into Salesforce with your System Administrator account.
2. Go to **App Launcher** and open **Cloud Protection**.
3. Go to **Administration > License**.

4. Depending on the number of licenses you have purchased, do one of the following:
 - If you have purchased WithSecure licenses for a limited number of users, set the License mode to **Selected users**, select **Save** and proceed to the next step.
 - If you have purchased WithSecure licenses for all users in your organization, set the License mode to **All users** and select **Save**.
5. Select the **Select licensed users** link.
The **Assign Licenses** window opens.
6. Search by the user name, profile, or department, or scroll through the list to find the users who need the license.
7. Select **Assign** in the Action column to assign the license to the selected user. You can also select **Assign All** to assign WithSecure Cloud Protection licenses to the list of users retrieved by your search.
8. Select **Close** when you are done.

You can consider turning on automatic license assignments on user profiles or other criteria:

a) Click **Manage automatic license assignments...**

b) Define the search criteria to add a new automatic license assignment rule.

You can use Name, Profile, Role, Email, Company, Division, and Licensed values for the search criteria. The search box supports partial and full matches:

- `Profile=System` finds any user whose profile name contains `System`, such as `System Administrator`.
- `Profile="System"` finds only users with a profile named `System`.
- You can use the percent sign as a wildcard to match any characters, for example `Profile=S%A` will find users with profiles like `System Administrator` but also `Standard User` and so on.

c) Click **Add**.

The rule is added to the table, and you can add more rules as needed.

Note: The rules you add are read using "OR" between the lines. In other words, the rules mean that licenses are assigned automatically to new users that only match one of the rules in the table. To define an "AND" condition, write the search criteria on the same line, for example "Profile=System, Department=Sales".

d) Switch on **Automatic license assignments** to take the specified rules into use.

When WithSecure licenses are assigned to a large number of users, the app assigns these licenses in the background and reports the status or any errors as alerts.

2.5 Upgrading the application

The latest version of the WithSecure Cloud Protection application is always available in Salesforce AppExchange. Upgrading the application from the previous version preserves all the existing settings and analytics data.

Note: You cannot upgrade from a release preview or beta version of the application. Uninstall the previous version and then install the new version of the application.

1. Log in to Salesforce with your System Administrator account.
2. Go to the Salesforce AppExchange marketplace, find the WithSecure Cloud Protection application, and select **Get It Now** to start installation.

WithSecure Cloud Protection is listed on Salesforce AppExchange here:

<https://appexchange.salesforce.com/listingDetail?listingId=a0N3A00000EFntJUAT>.

3. Depending on whether you are installing the application to your production Salesforce org or Sandbox, choose **Install in production** or **Install in Sandbox**.
4. Check the installation details.
5. Select **I have read and agree to the terms and conditions** and then select **Confirm and Install**.
6. Select **Install for Admins Only** and then select **Upgrade**.
7. Select **Yes, grant access to these third-party web sites** to allow the application to connect to the WithSecure Security Cloud services, and then select **Continue**.
8. Wait until the installation is complete.

Important: If you receive a message that the app is taking too long to install, wait for a confirmation email from Salesforce that the app has been installed.

9. Select **Done** when the installation is complete.

WithSecure Cloud Protection has been upgraded successfully.

Chapter 3

Configuring the application settings

Topics:

This section describes the application settings that you need to check and configure after the installation.

- [Configuring recipients for alerts and notifications](#)
- [Configuring security alerts and warning messages](#)
- [Setting up file protection](#)
- [Setting up URL protection](#)
- [Changing the settings for manual and scheduled scanning](#)
- [Creating a permission set for manual scanning](#)
- [Setting up automatic product updates](#)
- [Changing the privacy settings](#)

3.1 Configuring recipients for alerts and notifications

WithSecure Cloud Protection sends security alerts and user notifications by email.

Security alerts are sent to the WithSecure Cloud Protection Admins group. User notifications are sent to internal users within your Salesforce organization. You need to create an organization- wide email address that is used to send security alerts and user notifications from.

Note: The email address used for security alerts and user notifications must exist and be valid. You must verify the email address before Salesforce allows you to use it.

Follow these instructions to configure the WithSecure Cloud Protection Admins and email address to send security alerts and user notifications.

1. Log in to Salesforce with your System Administrator account.
2. Go to **App Launcher** and open **Cloud Protection**.
3. Go to **Administration > General**.
4. Open the **Notifications** panel.
5. Select the **WithSecure Cloud Protection Admins** link.
6. Select **Edit**, and add the users who will receive security alerts from WithSecure Cloud Protection and then select **Save**.
7. Go back to **Administration > General** and select **Configure organization-wide email addresses...** on the Notifications panel.
8. Next to **User Selectable Organization-Wide Email Addresses**, select **Add**.
9. Specify the display name and email address, and then select **Save**.
10. Go to **Administration > General Settings > General**.
11. Under **Notifications**, next to **Send email notifications from this address**, select the email address that you created previously.
12. Select **Save** to save the changes.

3.2 Configuring security alerts and warning messages

Follow these instructions to choose when to send alerts to administrators and users, and to edit the warning messages.

1. Go to **App Launcher** and open **Cloud Protection**.
2. Go to the **Administration > File Protection** tab.
3. Open **Notifications** to configure file protection alerts and messages.
 - Select **Send a security alert when harmful content is detected** to send an alert to administrators when harmful content is uploaded or downloaded from the Salesforce cloud.
 - Select **Send a security alert when disallowed content is detected** to send an alert to administrators when disallowed content is uploaded or downloaded from the Salesforce cloud.
 - Select **Send a warning message to internal users when they upload harmful content** to send an alert to users when they upload malicious content to the Salesforce cloud.
 - Select **Send a warning message to internal users when they upload disallowed content** to send an alert to users when they upload disallowed content to the Salesforce cloud.
 - Select **Send a security alert when content reputation changes** to send an alert to administrators when the reputation for a file changes.

If you have selected to remove harmful or disallowed files when the scan finds them, turn on **Replace removed harmful content with a text file** or **Replace removed disallowed content with a text file** to use a placeholder text file in place of the removed file. To edit the files, click **Configure file replacement**.

4. Go to the **Administration > URL Protection** tab.
5. Open **Notifications** to configure URL protection alerts and messages.
 - Select **Send a security alert when a harmful URL is detected** to send an alert to administrators when a harmful web link is published or clicked on the Salesforce cloud.
 - Select **Send a security alert when a disallowed URL is detected** to send an alert to administrators when a disallowed web link is published or clicked on the Salesforce cloud.

- Select **Send a warning message to internal users when they upload a harmful URL** to send an alert to users when they publish a harmful web link to the Salesforce cloud.
- Select **Send a warning message to internal users when they upload a disallowed URL** to send an alert to users when they publish a disallowed web link to the Salesforce cloud.
- Select **Send a security alert when the URL reputation changes** to send an alert to administrators when the reputation for a web link that has been published to the Salesforce cloud changes.

3.3 Setting up file protection

This section describes how to set up the basic File Protection scan settings.

Follow these instructions to configure how to scan files that are uploaded and downloaded from Salesforce.

1. Log in to Salesforce with your System Administrator account.
2. Go to **App Launcher** and open **Cloud Protection**.
3. Go to **Administration > File Protection**.
4. Depending on how the content that you want to check is stored, switch on **Scan content stored as Salesforce Attachments**, **Scan content stored as Salesforce Files**, or both.
5. If you are scanning attachments, select **Configure locations** to specify the sources of content that you want to check.
 - Choose **Selected objects** and select the sources that you want to check.
 - Choose **All objects** if you want to check all available attachments.
6. Click **Confirm**.
7. Turn on **Scan files for harmful content on upload** and **Scan files for harmful content on download**.
8. Select what happens when harmful content is found.
 - **Allow access** neither blocks nor removes harmful files that are found during the scan.
 - **Remove file** moves harmful files that are found during scanning to the quarantine.
 - **Block access** blocks all access to harmful files, but does not remove them.
9. If necessary, change the file types or file extensions that are scanned:
 - a) Select **All except excluded** or **Only included**.
 - b) Select **Configure excluded file types and extensions** or **Configure included file types and extensions**.
 - c) Specify the list of relevant file types or extensions.
Use the file type or file extension, for example WORD_X or docx.

Note: File type identification is based on the type as it is listed in Salesforce. To see examples of the file types, you can view the details of files listed on the **Analytics > File Events** page.

 - d) If the type or extension that you want is not listed, enter it in the text field and select **Add**.
 - e) Select **Save**.
10. To configure what WithSecure Cloud Protection does when it detects disallowed content that is uploaded or downloaded by Salesforce users:
 - a) Go to **Administration > File Protection**.
 - b) Turn on **Scan files for disallowed content on upload** and **Scan files for disallowed content on download**.
 - c) Select what happens when harmful content is found:
 - **Allow access** neither blocks nor removes disallowed files that are found during the scan.
 - **Remove file** moves disallowed files that are found during scanning to the quarantine.
 - **Block access** blocks all access to disallowed files, but does not remove them.
11. If necessary, change the file types or file extensions that you want to allow or disallow:
 - a) Select **Only disallowed** or **All except allowed**.
 - b) Select **Configure disallowed file types** or **Configure allowed file types**.
 - c) Specify the list of relevant file types or extensions.
Use the file type or file extension, for example WORD_X or docx.

- d) If the type or extension that you want is not listed, enter it in the text field and select **Add**.
- e) Select **Save**.

3.4 Setting up URL protection

This section describes how to set up the URL protection scan settings.

Follow these instructions to block harmful and disallowed links in your Salesforce organization.

1. Log in to Salesforce with your System Administrator account.
2. Go to **App Launcher** and open **Cloud Protection**.
3. Go to **Administration > URL Protection**.
4. Under **Targets**, select the types of message where you want to scan URLs.
5. To block access to harmful websites:
 - a) Under **URL Protection**, turn on **Check reputation of URLs**.
 - b) In **When URL is rated harmful**, select **Block access**.
6. To block websites with certain content:
 - a) Under **URL Protection**, turn on **Check category of URLs**.
 - b) In the **Select disallowed categories** list, select the content to block.
 - c) In **When a disallowed URL is found**, select **Block access**.
7. To allow access to certain websites, open **Exclusions**.
 - Turn on **Exclude trusted domains, hosts, and URLs** and select **Open the list of trusted domains, hosts, and URLs** to specify websites that are never blocked.
 - Turn on **Exclude domains that support rich link previews** and select **Open the list of domains** to specify websites that are allowed to embed videos, images, and article previews to posted links.
8. Open **Advanced** to check the settings there:
 - **Enable custom Chatter integration for processing posts and comments:** This setting is turned on by default. When the Enable custom Chatter integration for processing posts and comments setting is turned on and the changes are saved, the application automatically creates the WithSecure Cloud Protection Edit Chatter Posts permission set. You must assign it along with the WithSecure Cloud Protection User permission set to all users as described in the Assign WithSecure Cloud Protection User permission set section.
 - **Report excluded URLs in Analytics:** Turn this setting off if you do not want to show excluded URLs in the analytics reports.
 - **Show original URLs in redirect links:** Turn this setting off if you do not want to show the original URL in links.
9. Select **Save** to save all the changes.

3.5 Changing the settings for manual and scheduled scanning

Both manual and scheduled scans use the same shared settings for what is scanned, how detections are handled, and what notifications are sent.

1. Log in to Salesforce with your System Administrator account.
2. Go to **App Launcher** and open **Cloud Protection**.
3. Go to **Administration > Manual Scan**.
4. Under **Settings**, switch on **Scan files for harmful content**.

To configure the type of files that are scanned:

- a) Select **All except excluded** or **Only included**.
- b) Select **Configure excluded file types and extensions** or **Configure included file types and extensions**.
- c) Specify the list of relevant file types or extensions.

Use the file type or file extension, for example `WORD_X` or `docx`.

Note: File type identification is based on the type as it is listed in Salesforce. To see examples of the file types, you can view the details of files listed on the **Analytics > File Events** page.

- d) If the type or extension that you want is not listed, enter it in the text field and select **Add**.
 - e) Select **Save**.
5. Switch on **Scan files for disallowed content** if you also want to check for certain types of content.
- To set the type of files that are disallowed:
- a) Select **Only disallowed** or **All except allowed**.
 - b) Select **Configure disallowed file types** or **Configure allowed file types**.
 - c) Specify the list of relevant file types or extensions.
Use the file type or file extension, for example `WORD_X` or `docx`.
 - d) If the type or extension that you want is not listed, enter it in the text field and select **Add**.
 - e) Select **Save**.
6. Select what happens when the product finds harmful or disallowed content.
- **Report only** includes the detection in reports and notifications, but does not do anything to the file.
 - **Remove file** places the file in quarantine and also includes the detection in reports and notifications.
7. Set the notifications for scans.
- The notifications are sent to the recipients set in **Administration > General > Notifications**.
- To edit the notification templates, click **Configure security alert message** or **Configure file replacement** for the selected notifications.
8. Select **Advanced** and check the settings there:
- Turn on **Report harmful or disallowed content only** if you do not want the scan results to show clean or excluded files.
 - Turn on **Update hash checksums for scanned files** if you want to update the file modification timestamps for scanned files. This updates the **SHA** value for the scanned file, which also sets the time of the most recent change for the file.
 - Turn on **Maximum number of files per batch** if you want to define how many files are processed in one batch.
- Note:** Normally, this setting does not need changing. However, if the **Exceeded maximum time** error appears, it is recommended to decrease the value defined in this setting.

3.6 Creating a permission set for manual scanning

Manual and scheduled scanning with WithSecure Cloud Protection require special permissions that allow the processing of all files in Salesforce.

To create the set of required permissions:

1. Log in to Salesforce with your System Administrator account.
2. Go to your organization settings and select **Setup**.
3. Navigate to **Administration > Users > Permission Sets**.
4. Click **New** to create a new permission set.
5. Enter a **Label** and **API Name** for the new permission set.
For example, enter `WithSecure Cloud Protection Manual Scan` and use the automatically generated API name: `WithSecure_Cloud_Protection_Manual_Scan`.
6. Click **Save**.
7. On the page with the newly created permission set, click **App Permissions** under the **Apps** section.
8. On the **App Permissions** page, click **Edit**.
9. Under **Content**, select **Query All Files**.
10. Click **Save**.
11. Click **Save** in the **Permission Changes Confirmation** dialog to enable the additional system and object permissions.
The new permission set is now created.
12. Click **Manage Assignments** and assign the new permission set to the users who need to run manual or scheduled scans.

3.7 Setting up automatic product updates

Follow these instructions to set up automatic updates.

After a new version of the application has been validated internally and reviewed by the Salesforce security team, it is published in Salesforce AppExchange.

1. Go to **App Launcher** and open **Cloud Protection**.
2. Go to the **General** tab.
3. Open **Automatic updates**.
4. Turn on **Install product updates automatically** to receive new versions of the app automatically.
5. In **Preferred week day and time to install updates**, select the day and time when you want to have the new version installed to your Salesforce org environment.

Note: Updates are queued in Salesforce and may not take effect immediately at the preferred time. The exact time when updates are installed to your Salesforce org will depend on the upgrade queue. Per the product Lifecycle policy, WithSecure™ reserves the right to push product updates irrespective of the automatic update settings.

6. To check when updates have been installed successfully, go to **Analytics > Alerts**.

Note: When a new version is installed, the app sends an email notification to the users added to the WithSecure Cloud Protection Admins group.

3.8 Changing the privacy settings

Follow these instructions to choose what information you want to contribute to Security Cloud.

Security Cloud is an analytics engine and information repository for malware and a variety of other digital threats. Security Cloud's reputation services provide a fast way to identify known safe and malicious objects, it can perform both automated and manual analysis of suspicious objects, and it aggregates information on a global scale about objects in order to increase protection accuracy.

We apply a set of strict privacy principles to avoid collecting sensitive personal data and ensure that only essential technical data arrives on our servers.

1. Go to **App Launcher** and open **Cloud Protection**.
2. Go to the **Administration > General** tab.
3. Change the settings under **Privacy**.
 - a) WithSecure Cloud Protection primarily performs queries to Security Cloud with the hash of a file. Turn on **Send complete files for malware and advanced threat scanning** to send the complete file instead of just its hash for analysis. We recommend that you keep this option on to allow WithSecure Cloud Protection to detect advanced threats and complex malware as soon as possible. Files submitted for advanced threat scanning are deleted immediately after processing.
 - b) Turn on **Allow WithSecure Labs to collect suspicious executable files for analysis** to send unknown executable files for deeper analysis.
Interpreted code, like Flash, Silverlight, and scripts may also be handled as executable files.
 - c) Turn on **Allow WithSecure Labs to collect suspicious non-executable files for analysis** to send potentially harmful data files for deeper analysis.
 - d) Select what data you want to allow to be shared with third-party services when a file triggers a detection for threat analysis:
 - **Do not allow:** No data is shared with third-party services.
 - **Metadata only:** Only file metadata can be shared.
 - **Whole content:** Files can be shared.

Chapter 4

Using the application

Topics:

- [Excluding files from the scan](#)
- [Scanning for harmful content in your Salesforce organization manually](#)
- [Scanning for harmful content at set times](#)
- [Using the quarantine](#)
- [Viewing alerts and using the search](#)
- [Viewing and editing reports](#)
- [Clearing the scan result cache](#)
- [Viewing license information for the product](#)

This section describes various tasks related to the regular use of WithSecure Cloud Protection for Salesforce.

4.1 Excluding files from the scan

Sometimes you may want to exclude some file types or file extensions from the scan. Excluded files are not scanned unless you remove them from the excluded lists.

To exclude file types or file extensions from the scan:

1. Go to **App Launcher** and open **Cloud Protection**.
2. Find the file type or file extension to exclude:
 - a) Go to **Analytics > File Events**.
 - b) Select **View** at the end of the event row for a file that you want to exclude.
The **File Extension** and **File Type** are listed in the **File Event History** view, next to the **File Name**.
3. Go to the **Administration > File Protection** tab.
4. Open **Exclusions** to exclude files based on either their type or extension.
 - Turn on **Exclude files by file type**, select **Open the list of file types**, and specify file types that should not be scanned.
 - Turn on **Exclude files by file extension**, select **Open the list of file extensions**, and specify file extensions that are should not be scanned.

4.2 Scanning for harmful content in your Salesforce organization manually

In addition to automatically checking content that is uploaded, downloaded, or accessed in your organization, you can use the product to manually check the content that is stored in your organization.

Note: You must have special permissions assigned to your user account to use manual and scheduled scanning.

1. Log in to Salesforce with your System Administrator account.
2. Go to **App Launcher** and open **Cloud Protection**.
3. Go to **Administration > Manual Scan**.
4. Depending on how the content that you want to check is stored, switch on **Scan content stored as Salesforce Attachments**, **Scan content stored as Salesforce Files**, or both.
5. If you are scanning attachments, select **Configure locations** to specify the sources of content that you want to check.
 - Choose **Selected objects** and select the sources that you want to check.
 - Choose **All objects** if you want to check all available attachments.
6. Click **Confirm**.
7. Set the date range for the content to check and whether the date is based on when the content was created or when it was last modified.
8. Set **Maximum number of files to scan**.
9. Click **Scan now**.
A **Scan Job Started** notification appears.

There is no separate report of the scan results, but the **Analytics > File Events** page shows you any files that are processed during the scan. The **Direction** column shows **Scan Job** for events related to manual and scheduled scans.

Related tasks

[Creating a permission set for manual scanning](#) on page 16

Manual and scheduled scanning with WithSecure Cloud Protection require special permissions that allow the processing of all files in Salesforce.

4.3 Scanning for harmful content at set times

You can set up scheduled scanning tasks in Cloud Protection for Salesforce to check your organization's content at specific times.

Note: You must have special permissions assigned to your user account to use manual and scheduled scanning.

To create a new scheduled scanning task:

1. Log in to Salesforce with your System Administrator account.
2. Go to **App Launcher** and open **Cloud Protection**.
3. Go to **Administration > Manual Scan**.
4. Select **Scheduled Scanning** and then click **Create**.
This opens the **Schedule Apex** view, where you can set up your scheduled task.
5. Edit the **Job Name**.
6. Select **Weekly** or **Monthly** as the frequency.
7. Set the recurrence for the task.
8. Set the **Start** and **End** dates for the task.
9. Select the **Preferred Start Time**.
10. Click **Save**.

There is no separate report of the scan results, but the **Analytics > File Events** page shows you any files that are processed during the scan. The **Direction** column shows **Scan Job** for events related to manual and scheduled scans.

To edit the scheduled task later, click **View scheduled jobs** under **Scheduled Scanning** to open the **Schedule Apex** view, then click **Manage** for your task.

Related tasks

[Creating a permission set for manual scanning](#) on page 16

Manual and scheduled scanning with WithSecure Cloud Protection require special permissions that allow the processing of all files in Salesforce.

4.4 Using the quarantine

Cloud Protection for Salesforce moves detected harmful files to the quarantine so that they do not pose any further risk for your organization.

Note: The quarantine is based on the Salesforce recycle bin, so stored content is deleted permanently based on your organization's settings for the recycle bin. You should check the quarantine as soon as possible after receiving alerts of harmful files to make sure that you can check the file if necessary before it is deleted permanently.

To view quarantined content:

1. Log in to Salesforce with your System Administrator account.
2. Go to **App Launcher** and open **Cloud Protection**.
3. Go to **Administration > Quarantine**.

Click **View** to see the details for a file.

To permanently delete a file:

- a) Select the files that you want to delete.
- b) Click **Delete**.
- c) Click **Confirm**.

To restore a quarantined file:

- a) Select the files that you want to restore.
- b) Click **Restore**.

This returns the selected files to their original location and allows you to access them again.

4.5 Viewing alerts and using the search

Follow these instructions to view security alerts.

1. Go to **App Launcher** and open **Cloud Protection**.
2. Go to the **Analytics** tab.
 - The **Alerts** view shows all security alerts.
 - The **File Events** view shows all events from the file scan.

- The **URL Events** view shows all events from the web link reputation and category checks.
3. Click **View** at the end of the alert or event row to see the full details of the alert or the event history.
 4. Use search values to narrow down the listed results.
 - Supported values for the **Alerts** view: TIME, SEVERITY, SOURCE, USER, REASON.
 - Supported values for the **File Events** view: TIME, ACTION, VERDICT, FILENAME, FILETYPE, DIRECTION, LOCATION, SHA1, USER, IPADDRESS.
 - Supported values for the **URL Events** view: TIME, ACTION, VERDICT, URL, DIRECTION, LOCATION, USER, IPADDRESS, CATEGORY.
 - To search events on a certain date and time, use the date and time values based on your current locale. The search supports all Salesforce SOQL date literals.

Search examples:

- Find critical alerts that are related to the file protection in the **Alerts** view: SEVERITY=Critical, SOURCE=File Protection
- Find all uploaded files that have been blocked in the **File Events** view: ACTION=Blocked, DIRECTION=Upload
- Find all blocked download attempts for the Sales_Report.xlsx file in the **File Events** view: ACTION=Blocked, DIRECTION=Download, FILENAME=Sales_Report.xlsx
- Find all blocked URLs that have been posted by users in the **URL Events** view: ACTION=Blocked, DIRECTION=Post
- Find all URLs that have been opened from the IP address 192.168.0.1 in the **URL Events** view: DIRECTION=Open, IPADDRESS=192.168.0.1

Date and time search examples (locale: English (United Kingdom))

- TIME=31/12/2016 12:00
- TIME=31/12/2016 12:00...12/12/2016 14:00
- STARTTIME=31/12/2016 12:00
- ENDTIME=31/12/2016 12:00
- TIME=31/12/2016>5d
- TIME=31/12/2016 12:00>5h
- TIME=YESTERDAY

4.6 Viewing and editing reports

WithSecure Cloud Protection's reporting provides information that is useful both in getting a quick overview of the protection status and in investigating or responding to an attack.

The reporting information includes infection-related statistics, such as infections found and their sources, a comparison of the trends between safe and unsafe files, as well as the amount of currently protected files. WithSecure Cloud Protection for Salesforce also reports the most commonly used file types, the most frequently occurring sources, and the most active users.

Follow these instructions to view reports for WithSecure Cloud Protection for Salesforce.

1. Go to **App Launcher** and open **Cloud Protection**.
2. Go to the **Summary** tab.

The **Summary** view shows the all-time statistics of scanned files and blocked URLs, and the total number of alerts.

Note: It is a good idea to monitor the number of alerts, especially those listed as **Critical** and **Important**. Sudden increases in these numbers may indicate security issues within your organization.

3. To see a filtered view of a specific type of alert, click the corresponding number in the **Alerts** table.
4. Click the **More reports** drop-down and select a report to view the protected content analytics and more details of file and URL protection.

Each of these reports contains a number of charts and graphs that provide details of the protection status of your organization. You can edit the reports and save them as new, customized reports if necessary.

To schedule email delivery of a report:

- a) Click **Subscribe**.
- b) Set the frequency and time for sending the report.
- c) Click **Edit Recipients** and add any other users who should receive the report.
- d) Click **Save**.

To create a new report using the available attributes:

- a) Click the drop-down icon next to **Subscribe** and select **New Dashboard**.
- b) Enter a name and description for the report and select a folder, then click **Create**.
- c) Use the **Component** and **Filter** options on the toolbar to select what to include in the report.
- d) Click **Save**.
- e) Click **Done** when you have finished editing the report.

Attributes for file reports:

- Created By: Full Name
- Created Date
- Date/Time
- File Extension
- File Name
- File Scan ID
- File Size
- File Type
- IP Address
- Last Modified By: Full Name
- Last Modified Date
- Name
- Owner: Full Name
- Record Id
- Scan Type
- SHA1
- Location
- User: Full Name
- Verdict
- Owner (First Name, Full Name, Last Name, Owner ID, Phone, Profile: Name, Rule: Name, Title, Username, Email, Alias, Active)
- Reason
- File Prevalence
- File Reputation Rating

Attributes for URL reports:

- URL Scan: ID
- URL Scan: Name
- Action
- Categories
- Date/Time
- Direction
- IP Address
- Location
- Reason
- Reputation
- Reputation Description
- URL
- User
- Verdict
- Owner Name

- Owner Alias
- Owner Role
- Created By
- Created Alias
- Created Date
- Last Modified By
- Last Modified Alias
- Last Modified Date

4.7 Clearing the scan result cache

WithSecure Cloud Protection stores its scan results in the scan result cache to optimize performance. This cache is cleaned up periodically, but you may want to delete all scan results from the cache manually, for example while testing the product.

1. Go to **App Launcher** and open **Cloud Protection**.
2. Go to the **Administration > Tools** tab.
3. Under **Clean up scan result cache**, click **Start**.
4. To set how long scan results are stored in the cache:
 - a) Go to the **Administration > General > Advanced** tab.
 - b) In **Expiration time (TTL) for scan results in the cache**, select how long scan results are stored in the cache.

4.8 Viewing license information for the product

The **License** page in WithSecure Cloud Protection for Salesforce includes details on your license status and usage.

1. Log in to Salesforce with your System Administrator account.
2. Go to **App Launcher** and open **Cloud Protection**.
3. Go to the **Administration > License** page.

This page shows you the current status and expiration date for your license, as well as information on the license usage and scanning usage statistics.

Related tasks

[Assign WithSecure Cloud Protection licenses](#) on page 9

WithSecure Cloud Protection licenses must be assigned to all users who administer the application or who are protected against security threats associated with harmful and disallowed content.

Chapter 5

Testing the application

Topics:

- [Testing the file protection](#)
- [Testing the URL protection](#)

After you have installed and configured the WithSecure Cloud Protection application, test that the file protection and the URL protection are working.

5.1 Testing the file protection

Follow these instructions to test the file protection with the Eicar test file.

1. Download the Eicar.com test file from https://www.eicar.org/?page_id=3950 and rename it to `Example_MaliciousFile.docx`.
Note: Even though it is not harmful, Eicar.com is identified as malware for testing purposes. If your anti-malware protection blocks the file, exclude a folder from real-time scanning and place the Eicar.com file there.
2. Upload `Example_MaliciousFile.docx` and any clean file to Salesforce Files or Chatter.
3. Go to **App Launcher** and open **Cloud Protection**.
4. Go to the **Analytics > File Events** tab.
This shows you one clean file and one blocked file.
5. Try to download both files.
You can download the clean file, but the malicious file is blocked.
6. Go back to the **Analytics > File Events** tab to see the download events.
7. Click **View** to see the full event history.
This shows you all upload and download actions for the selected file.

5.2 Testing the URL protection

Follow these instructions to test the URL protection using the test domains.

1. Go to **App Launcher** and open **Cloud Protection**.
2. Go to the **Administration > URL Protection** tab.
3. For this test, make sure that Gambling is selected in the **Select disallowed categories** list.
4. Post two example URLs `unsafe.fstestdomain.com` and `gambling.fstestdomain.info` to Salesforce Chatter.
5. Open Chatter to see two new posts where URLs has been rewritten.
6. Go back to **WithSecure Cloud Protection** and go to the **Analytics > URL Events** tab.
This shows you two new Chatter posts.
7. Go back to Chatter and try to open both links. You will see Harmful web site blocked and Disallowed web site blocked block pages.
8. Go back to **WithSecure Cloud Protection** and go to the **Analytics > URL Events** tab again.
This shows you two URL opening events.
9. Click **View** to see the full event history.
This shows you all posting and opening actions for the selected URL.

Chapter 6

Uninstallation

Topics:

- [Removing permission set assignments](#)
- [Uninstalling the application](#)

This section provides instructions for removing WithSecure Cloud Protection from your Salesforce organization.

Removing the application involves the following steps:

- Remove permission set assignments
- Uninstall the application

6.1 Removing permission set assignments

Before uninstalling the WithSecure Cloud Protection application, you must remove WithSecure Cloud Protection User and WithSecure Cloud Protection Admin permission sets, which you assigned to users within your Salesforce organization.

To remove the permission sets:

1. Log in to Salesforce with your System Administrator account.
2. Go to **App Launcher** and open **Cloud Protection**.
3. Go to **Administration > Tools** and under **Manage user permission set**, select **Remove**.
4. Go to your organization settings and click **Setup**.
5. Select **Users > Permission Sets > WithSecure Cloud Protection Admin**.
6. Click **Manage Assignments**.
7. Select all users and click **Remove Assignments**.
8. Click **OK** to confirm that you want to remove all users.

6.2 Uninstalling the application

After you have removed all user permissions, you need to uninstall the WithSecure Cloud Protection application.

Follow these instructions to uninstall the WithSecure Cloud Protection application:

1. Log into Salesforce with your System Administrator account.
2. Go to your organization settings and select **Setup**.
3. Go to **Apps > Installed Packages**.
4. Next to WithSecure Cloud Protection, select **Uninstall**.
5. On the **Uninstalling a Package** page, scroll down and select **Yes, I want to uninstall this package and permanently delete all associated components**.

You receive an email notification when the **WithSecure Cloud Protection** application has been uninstalled.